

YOUR RELIABLE GLOBAL PARTNER



Related Products





FR-2000







endance



Temperature


















 $\label{eq:Face record} \textbf{Face record function for strangers, more safer}.$



Supports content management system





Specification

System


| Size | 8.0 inch |
|----------------------------|--|
| Resolution | 800×1280 |
| CPU | Rk3288 four cores |
| Local storage | EMMC 8G |
| Pixels | 2,000,000 |
| Туре | Binocular wide dynamic camera |
| Focus distance | 50-150cm |
| White balance | Auto |
| Fill light | LED and infrared double fill light |
| Network module | Support Ethernet, wireless (WiFi) |
| Audio | Support 2.5W/4R horn |
| USB | 1*USB OTG,1*USB HOST Standard A port |
| Serial | 1*RS232 |
| Relay output | 1 |
| Wiegand interface | 1*26/34 output,1*26/34 input |
| Upgrade button | Sport Uboot upgrade button |
| LAN | 1*RJ45 |
| Function | |
| Face detection | Support multiple people detection and tracking |
| Face atabasecapacity | 30 thousands |
| 1:N Face recognition | Supported |
| 1:1face-matching | Supported |
| Stranger detection | Supported |
| Detection distance | Supported |
| configuration | Supported |
| UI interface configuration | Supported |
| Device interface | Interface includes equipment management, personnel / photo management, record query, etc |
| Deployment mode | Support public cloud deployment, private deployment, LAN use, stand-alone use |
| Mechanical | |
| Working temperature | 10 °C~60 °C |
| Storage temperature | -20°C~60 °C |
| Consumption | 13.5W(Max) |
| Mounting type | Gate support installation |
| Dimension | 238.24*128*25(mm) |
| Weight | 1.45kg |

Optional Accessories











Alcohol sprayer

Wall mount Communication module

NFC Card Reader

Authorized Distributor/Reseller







